



*City of Hesperia*  
**BUILDING AND SAFETY DIVISION**

**Single Family Residential Infill  
Erosion & Sediment Control Notes**

1. In case of emergency, call (Responsible Person) at (24-Hour telephone)
2. Pollution and erosion prevention measures, also known as Best Management Practices (BMPs), must be installed prior to grading. These measures, including the prevention of sedimentation or flood damage, to offsite property shall be adequate whether or not an erosion control permit is required per City of Hesperia Municipal Code chapter 8.30.
3. Eroded sediments and other pollutants must be retained onsite and may not be transported from the site via sheet flow, swales, area drains, natural drainage courses, or wind.
4. Erosion and sediment control BMPs shall be functioning at all times. In case of BMP failure, BMP repair shall be completed promptly.
5. Stockpiles of earth and other construction-related materials must be protected from being transported from the site by the forces of wind or water.
6. Fuels, oils, solvents, and other toxic materials must be stored in accordance with their listing and are not to contaminate the soils and surface waters. All approved storage containers are to be protected from the weather. Spills must be cleaned up immediately and disposed of in proper manner. Spills may not be washed into the drainage system or other public way.
7. Excess or waste concrete must be contained onsite. Provisions shall be made to retain concrete wastes onsite until they can be disposed of as solid waste.
8. Developers/contractors are responsible to ensure all Erosion Control BMPs are installed and functioning properly per plan. Proper precaution shall be considered when 50% or greater probability of predicted precipitation, and after actual precipitation.
9. Trash and construction-related solid wastes must be deposited into a covered receptacle to prevent contamination of rainwater and dispersal by wind.
10. Sediments and other materials may not be tracked from the site by vehicles traffic. The construction entrance roadways must be stabilized so as to inhibit sediments from being deposited into the public way. Accidental depositions must be swept up immediately and may not be washed down by water, rain or other means.
11. Any slopes with disturbed soils or denuded of vegetation must be stabilized so as to inhibit erosion by wind and water.
12. All storm water capture devices shall be protected at all times.